


# 584070

## Mobile dust extractor

### CTL 48 E



#### Performance features



#### Strengths and benefits

- Approved for dust category L
- Approval for dust class L or M
- Antistatic function prevents static developing during work
- Constantly high suction because of the compact high performance turbine
- Attachment of Systainers via Sys-Dock
- Hose garage, cord holder and handle
- Economical because of the optimal use of the available volume with a SELFCLEAN filter bag in the container

#### Main applications

- For dust with limit values  $> 1 \text{ mg/m}^3$
- For dust with limit values  $> 1 \text{ mg/m}^3$  (CTL) or  $> 0.1 \text{ mg/m}^3$  (CTM)
- Container volume of 48 litres for flexibility and cleanliness in the workshop
- Integral automatic electronic switch-on/shut-off for extraction from electric power tools
- Suitable for both wet and dry extraction

#### Items Included

- SELFCLEAN filter bag
- suction hose  $\varnothing 27 \text{ mm} \times 3,5 \text{ m-AS}$
- hose holder
- Sys dock
- cable holder
- handle

#### Packaging

in a carton

#### Technical data

Power consumption	350-1200	W
Airflow max.	3900	l/min
Max. vacuum	24000	Pa
Filter surface area	6318	cm <sup>2</sup>
Rubber-insulated mains cable	7,5	m
Container/Filter bag capacity	48/46	l
Dimensions (L x W x H)	740 x 406 x 1005	mm
Max. appliance socket connected load	2400	W
weight	18,8	kg

