

561285

Sliding compound mitre saw

KS 120 EB GB 240V



Performance features



Strengths and benefits

- Twin-column guide for accurate cuts
- Compact, lightweight design for convenient transportation
- FastFix saw blade changing for adaptation to the working material
- Precision angle transfer via bevel and dual-line laser
- Fine adjustment of the saw blade angle accurate to the millimetre from the front of the machine
- Safety brake

Main applications

- Trimming skirting boards and cornices up to 120 mm in height – no calculations
- Cutting boards and panels up to 305 x 88 mm
- Trimming crown mouldings up to 168 mm in their original wall position
- Trimming square timber and beams up to 88 mm thick

Items Included

- HW universal saw blade W60
- bevel
- workpiece clamp
- operation tool

Packaging

in a carton

Technical data



| | | |
|-----------------------------------|-----------------|-------|
| Power consumption | 1600 | W |
| Idle engine speed | 1400-3400 | min-1 |
| Saw blade diameter | 260 | mm |
| Cutting depth 90°/90° | 305 x 88 | mm |
| Cutting depth at 45°/90° | 215 x 88 | mm |
| Special cutting depth 90°/90° | 60 x 120 | mm |
| Crown moulding dia. cut 45°/90° | 168 | mm |
| Inclination angle | 47/47 | ° |
| Dimensions (W x D x H) | 713 x 500 x 470 | mm |
| Connection Ø d/e | 27/36 | mm |
| weight | 21,5 | kg |
| Special cut. depth 45°/90° (left) | 40 x 120 | mm |
| Special cutting depth 45°/90° | 20 x 120 | mm |
| Cutting depth 50°/90° (left) | 196 x 88 | mm |
| Cutting depth 60°/90° (right) | 152 x 88 | mm |
| Cutting depth 45°/45° (left) | 215 x 55 | mm |
| Cutting depth 45°/45° (right) | 215 x 35 | mm |

| | | |
|--|-------|----|
| Crown moulding diagonal cut at 90°/90° | 168 | mm |
| Mitre angle | 50/60 | ° |
| Bench height (on MFT) | 790 | mm |
