



CHARACTERISTICS

- Reactive primer
- Improves the adhesion of polyurethane sealants and hybrid sealants on several surfaces
- Contains solvents

APPLICATIONS

- Can be used as primer for **Detaflex** and **Parabond**
- Can be applied on several materials : plastics, concrete, brick, wood, etc.
- In case of porous surfaces, the **Primer DL 2001** should be painted in 2 layers.
- For use on metals, a preliminary test must be done on the material.
- Can also be used to prevent the migration of plasticizers.

TECHNICAL CHARACTERISTICS	
Base	Polyurethane
Colour	Black or transparent
Density	0.92 g/cm ³ at 20°C
Viscosity	Ca 50 mPa.s
Drying time	10 - 15 minutes
Flash point	< 21°C
Shelf life after opening	24 h
Shelf life, in the original closed packing between 0°C - +35°C	Min. 12 months

PACKING AND COLOURS
12 cans of 250 ml/box - 27 boxes/pallet
Transparent, black
8 cans of 1 l/box - 27 boxes/pallet
Transparent, black

METHOD OF USE

Preparation

The surface must be dry and free of grease, oil and other dirt.
For use on metals, a preliminary test must be done on the material.

Application

- Shake the bottle vigorously before use
- Apply with a brush
- After drying (10 - 15 minutes), apply the sealant within a one hour deadline
- In case of porous surfaces, the **Primer DL 2001** should be painted in 2 layers.
- Make sure the packaging is closed correctly after use. After opening of the bottle, the product must be used within 24 hours

Cleaning

It is possible to clean with White Spirit within the first 5 minutes. After that a cleaning with MEK is required.

SAFETY

Safety data sheet available on request.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.